

HAND PROTECTION GREEN LATEX GLOVE

PRODUCT DATA SHEET: GL-(SIZE)

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
GL-(SIZE)



FEATURES AND BENEFITS

- AS/NZS 2161.3:2005 Occupational Protective Gloves Against Mechanical Risks.
- Certified to EN420 AS/NZS 2161.2:2005 General Requirements.
- Certified to EN388 AS/NZS 2161.3:2005 Protection Against Mechanical Risks Results - 4141.
- Certified to EN 407 AS/NZS 2161.4:1999 Protection Against Thermal Risks (Heat & Fire)
Results: X2XXXX
Contact Heat to 250°C
- Certified to EN ISO 374-1 AS/NZS 2016 Protection Against Micro Organisms Risks
Results: AKLMNPT Type A
- Certified to EN ISO 374-5 AS/NZS 2016 Protection Against Micro Organisms Risks
- Crinkled palm enhances protection and grip.
- Fully coated for extra protection.
- Cotton interlock liner absorbs perspiration and improves comfort.
- 2 piece liner without seams in the working area eliminates discomfort.
- Anatomically shaped to provide good fit.
- Extended gauntlet cuff to protect forearm.
- Liquid proof for use in wet conditions.
- Durable and washable.

PRODUCT DETAILS

Material: Natural rubber
Thickness: 1.8 mm +/- 0.15
Lining: Cotton Interlock
Cuff Type: Gauntlet
Finish: Crinkled finish
Colours: Green

APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Deep sea fishing, Oyster farming, Forestry and timber, Glass and Metal industry, Quarrying and Mining.



ABRASION
RESISTANT



HEAT
RESISTANT



CHEMICAL
RESISTANT



MACHINE
WASHABLE

AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
GL-(SIZE)	GREEN	PAIR	12	60

PHYSICAL DIMENSIONS

SIZE	PALM	WRIST	CUFF	GLOVE LENGTH
6	195mm +/- 5mm	182mm +/- 5mm	249mm +/- 5mm	300mm +/- 10mm
7	208mm +/- 5mm	216mm +/- 5mm	274mm +/- 5mm	300mm +/- 10mm
8	222mm +/- 5mm	228mm +/- 5mm	288mm +/- 5mm	300mm +/- 10mm
9	234mm +/- 5mm	240mm +/- 5mm	296 mm +/- 5mm	300mm +/- 10mm
10	242mm +/- 5mm	254mm +/- 5mm	304mm +/- 5mm	300mm +/- 10mm
11	272mm +/- 5mm	290mm +/- 5mm	316mm +/- 5mm	300mm +/- 10mm

Palm, wrist & cuff circumference measurements in mm. +/- 5 mm

STANDARDS

CE CATEGORY II:

Intermediary risk in accordance with:

AS/NZS 2161.3:2005 Occupational Protective Gloves Against Mechanical Risks.

EN420 AS/NZS 2161.2:2005 General Requirements

EN388 AS/NZS 2161.3:2005 Protection Against Mechanical Risks Results - 4141


EN 407 AS/NZS 2161.4:1999 Protection Against Thermal Risks (Heat & Fire)

Results: X2XXXX

Contact Heat to 250°C

EN ISO 374-1 AS/NZS 2016 Protection Against Micro Organisms Risks Results: AKLMNPT Type A

EN ISO 374-5 AS/NZS 2016 Protection Against Micro Organisms Risks



PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS